

# 100 WATT LED FORWARD THROW WALL PACK



**JAYKAL**

PROJECT NAME:

**JAYKAL LED SOLUTIONS, INC.**

[www.jaykal.net](http://www.jaykal.net)

PROJECT NOTES:

26832 Lewes Georgetown Hwy,  
Building 2, Unit E  
Harbeson, DE 19951  
(P) 302-295-0015  
(F) 302-295-0016

## FEATURES & BENEFITS:

- ◆ Lumileds LEDs Offer High Luminous Efficiency and Long Life.
- ◆ High Efficiency LED Driver
- ◆ Available with 100-277VAC or 200-480VAC Input
- ◆ Cast Aluminum Construction Provides Superior Cooling Performance, LED Tj<85
- ◆ Excellent Optical Design Optimizes Light Utilization and Distribution.
- ◆ Photocell Control Available (Option)



## PRODUCT APPLICATIONS

JAYKAL LED Wall Pack Lighting can be widely used in outdoor lighting locations. Ideal for wet locations requiring IP65 protection, they provide an excellent solution for applications such as security lighting, area lighting and landscape lighting.



5 YEAR STANDARD WARRANTY—EXTENDED WARRANTIES AVAILABLE

(P) 302-295-0015 | (E) [sales@jaykal.net](mailto:sales@jaykal.net) | (W) [www.jaykal.net](http://www.jaykal.net)

*Specifications are typical values and may change without notification*

**efficiency. illuminated.**



# 100 WATT LED FORWARD THROW WALL PACK



**JAYKAL**

**SPECIFICATIONS TABLE**

Watt	100W	Lumens	11,000 lm	Efficacy	110 lm/W
Input Voltage	100-277VAC 50/60hz	Power Factor	0.95	CRI	> 80
THD	<14%	CCT	3000K/4000K/5000K/6500K		
Life (L70)	50,000+ hours	Illumination Angle	60°90°	Operational Temperatures	-30° - +45°C
Housing Finish	Bronze / White	Lens Finish	Brown / Custom	Protection	IP65
Housing Material	Aluminum Die-cast	Lens Material	Polycarbonate	Environment	Wet Locations
Weight	13.89 lbs. / 6.3 kg	Dimensions	14.57 x 7.76 x 8.94 in / 370 x 197 x 227mm		
UL File No	E360683	Warranty	5 Years		



## ORDERING INFORMATION

EXAMPLE: JLS68103-G2FT-100-277-50K-D-PC

MODEL NUMBER	-	VOLTAGE	-	CCT	-	FINISH	-	CONTROL
JLS68103-G2FT-100		<b>277</b> = AC120-277VAC <b>480</b> = AC200-480VAC		<b>30K</b> = 3000K <b>40K</b> = 4000K <b>50K</b> = 5000K <b>65K</b> = 6500K		<b>D</b> = Dark Bronze <b>W</b> = White		<b>PC</b> = Photocell

(P) 302-295-0015 | (E) sales@jaykal.net | (W) www.jaykal.net

Specifications are typical values and may change without notification

efficiency. illuminated.




# 100 WATT LED FORWARD THROW WALL PACK



JAYKAL

## PHOTOMETRY

### Luminous Intensity Distribution



(P) 302-295-0015 | (E) sales@jaykal.net | (W) www.jaykal.net

Specifications are typical values and may change without notification

efficiency. illuminated.