

150 WATT LED FORWARD THROW WALL PACK



JAYKAL

PROJECT NAME:

JAYKAL LED SOLUTIONS, INC.

www.jaykal.net

PROJECT NOTES:

26832 Lewes Georgetown Hwy,
Building 2, Unit E
Harbeson, DE 19951
(P) 302-295-0015
(F) 302-295-0016

FEATURES & BENEFITS:

- ◆ Lumileds LEDs Offer High Luminous Efficiency and Long Life.
- ◆ High Efficiency LED Driver
- ◆ Available with 100-277VAC or 200-480VAC Input
- ◆ Cast Aluminum Construction Provides Superior Cooling Performance, LED Tj<85
- ◆ Excellent Optical Design Optimizes Light Utilization and Distribution.
- ◆ Photocell Control Available (Option)



PRODUCT APPLICATIONS

JAYKAL LED Wall Pack Lighting can be widely used in outdoor lighting locations. Ideal for wet locations requiring IP65 protection, they provide an excellent solution for applications such as security lighting, area lighting and landscape lighting.



5 YEAR STANDARD WARRANTY—EXTENDED WARRANTIES AVAILABLE

(P) 302-295-0015 | (E) sales@jaykal.net | (W) www.jaykal.net

Specifications are typical values and may change without notification

efficiency. illuminated.

150 WATT LED FORWARD THROW WALL PACK





JAYKAL

JLS68103-G2FT-150

SPECIFICATIONS TABLE

| | | | | | |
|------------------|---------------------|--------------------|--|--------------------------|---------------|
| Watt | 150W | Lumens | 16,000 lm | Efficacy | 107 lm/W |
| Input Voltage | 100-277VAC 50/60hz | Power Factor | 0.95 | CRI | > 80 |
| THD | <14% | CCT | 3000K/4000K/5000K/6500K | | |
| Life (L70) | 50,000+ hours | Illumination Angle | 60°90° | Operational Temperatures | -30° - +45°C |
| Housing Finish | Bronze / White | Lens Finish | Brown / Custom | Protection | IP65 |
| Housing Material | Aluminum Die-cast | Lens Material | Polycarbonate | Environment | Wet Locations |
| Weight | 14.99 lbs. / 6.8 kg | Dimensions | 14.57 x 7.76 x 8.94 in / 370 x 197 x 227mm | | |
| UL File No | E360683 | Warranty | 5 Years | | |



ORDERING INFORMATION

EXAMPLE: JLS68103-G2FT-150-277-50K-D-PC

| MODEL NUMBER | - VOLTAGE | - CCT | - FINISH | - CONTROL |
|-------------------|--|--|--|-----------------------|
| JLS68103-G2FT-150 | 277 = AC120-277V 480 = AC200-480V | 30K = 3000K 40K = 4000K 50K = 5000K 65K = 6500K | D = Dark Bronze W = White | PC = Photocell |

(P) 302-295-0015 | (E) sales@jaykal.net | (W) www.jaykal.net

Specifications are typical values and may change without notification




efficiency. illuminated.

150 WATT LED FORWARD THROW WALL PACK



PHOTOMETRY

Luminous Intensity Distribution



(P) 302-295-0015 | (E) sales@jaykal.net | (W) www.jaykal.net

Specifications are typical values and may change without notification

efficiency. illuminated.