G2 VAPOR TIGHT FIXTURE



	JAYKAL	
PROJECT NAME:	JAYKAL LED SOLUTIONS, INC. www.jaykal.net	
PROJECT NOTES:	21499 Baltimore Ave.	
	Georgetown, DE 19947	
	(P) 302-295-0015	
	(F) 302-295-0016	

FEATURES

- Wattages Selectable Available 12W 120W
- ♦ Voltage Input 120-277VAC 50/60Hz
- ♦ CCT Selectable 3000K/4000K/5000K
- ♦ IP65 Rating, IK08 Rating
- Polycarbonate Construction with Integrated Powder Coated Lighting Tray
- ♦ Stainless Steel Clips













Revised 12/11/23

G2 VAPOR TIGHT FIXTURE

FCC CERTIFICATION



				JAYKAL						
SPECIFICATIONS TABLE										
MODEL	JLS-G2VT SERIES									
ТҮРЕ	M1	M2	M3	M4						
WATTAGE	12W/16W/20W	22W/30W/40W	32W/40W/50W	80W/100W/120W						
VOLTAGE	100-277VAC 50/60HZ									
EFFICACY	130lm/W (Frosted)/150lm/W (Clear)	130lm/W (Frosted) / 150lm/W (Clear)	130lm/W (Frosted) / 150lm/W (Clear)	130lm/W (Frosted) /150lm/W (Clear)						
LUMENS (FROSTED)	1,560lm/2,080lm/2,600lm	2,860lm/3,900lm/5,200lm	4,160lm/5,200lm/6,500lm	10,400lm/13,000lm/15,600lm						
LUMENS (CLEAR)	1,800lm/2,400lm/3,000lm	3,300lm/4,500lm/6,000lm	4,800lm/6,000lm/7,500lm	12,000lm/15,000lm/18,000lm						
POWER FACTOR	>0.90									
DRIVER EFFICIENCY	>85%									
0-10V CURRENT	<1mA									
CRI	>80									
BEAM ANGLE	120°									
L70 HOURS	>100,000									
сст	MCCT (3000K/4000K/5000K Selectable)									
SPECIFIED LIGHT (OPTIONAL)	Green LED Light (Wavelength Range 520-525nm)									
WORKING TEMP.	-20°C—50°C									
IP RATING	IP65—Wet Locations									
HOUSING	Polycarbonate—Surface Mount / Chain / J-Box Mounting									
LENS	Frosted or Clear Polycarbonate									
DIMENSIONS (in.)	23.6″L x 4.92″W x 3.62″H (2 Ft.) / 47.2″L x 4.92″W x 3.62″H (4 Ft.) / 94.4″L x 4.92″W x 3.62″H (8 Ft.)									


ORDER	ORDERING GUIDE EXAMPLE: JLS-G2VT-4-M2-277-MCCT-F-10-N-I							-F-10-N-N
MODEL	LENGTH	WATTAGE	VOLTAGE	сст	LENS	DIM- MING	SENSOR	OPTION
JLS-G2VT	2 = 2 Ft. 4 = 4 Ft. 8 = 8 Ft.	M1 = 12W/16W/20W* M2 = 22W/30W/40W** M3 = 32W/40W/50W** M4 = 80W/100W/120W*** * For 2ft only *** For 4ft only *** For 8ft only	277 = 100-277VAC 347 = 100-347VAC * * For 4ft only	MCCT = 3000K/4000K/5000K G = Green LED Light	C = Clear F = Frosted	10 = 0-10V	N = No Sensor M = Motion Sensor	N = No Option EM = Emergency Battery Backup


FCC Title 47 CFR Part 18 Compliance

G2 VAPOR TIGHT FIXTURE



DIMENSIONS





8 Ft.