STRIP RETROFIT KIT



	JAYKAL
PROJECT NAME:	JAYKAL LED SOLUTIONS, INC.
	www.jaykal.net
PROJECT NOTES:	26832 Lewes Georgetown Hwy,
	Building 2, Unit E
	Harbeson, DE 19951
	(P) 302-295-0015
	(F) 302-295-0016

FEATURES & BENEFITS

- ♦ Available in 10W to 60W Fixed Wattage or with Multi-Wattage Driver
- ♦ CCT: 3000K, 3500K, 4000K, 5000K
- ♦ 130+lm/W
- ♦ 0-10V Dimming optional
- ♦ 5 Year Standard Warranty with 10 Year Available
- Replacement Housings for existing strip fixtures are available by request. Please add an H to the end of the part number.













Revised 1/20/21

STRIP RETROFIT KIT



IAYKAL

SPECIFICATIONS TABLE							
MODELS	JLS68102-STR (10W-60W)						
INPUT VOLTAGE	100-277VAC 50/60hz						
WATTAGE	M1 (12W/16W/20W/24W)	M2 (18W/24W/30W/36W)	M3 (24W/30W/36W/40W)	M4 (40W/45W/50W/60W)			
LENGTHS	2/3/4 Foot	3/4/8 Foot	3/4/8 Foot	4/8 Foot			
EFFICACY	130lm/W						
LUMENS	1,560LM to 3,120LM	2,340LM to 4,680LM	3,120LM to 5,200LM	5,200LM to 7,800LM			
L70 HOURS	113,000 hrs. +						
POWER FACTOR	>0.9						
THD	<15%						
CRI	>80						
ССТ	3000K/4000K/5000K						
OPERATIONAL TEMP.	-30°C - 50°C						
HOUSING MATERIAL	Steel						





ORDERING GUIDE										
MODEL	- WATTAGE	- LENGTH	- ССТ	- DIMMING	- CHANNEL WIDTH	- OPTIONS				
JLS68102-STR	VARIABLE WATTAGE M1 = (12W/16W/20W/24W) M2 = (18W/24W/30W/36W) M3 = (24W/30W/36W/40W) M4 = (40W/45W/50W/60W) VARIABLE WATTAGE EMERGENCY EM1 = (12W/16W/20W/24W) EM2 = (18W/24W/30W/36W) EM3 = (24W/30W/36W/40W) EM4 = (40W/45W/50W/60W) FIXED WATTAGE XX = May be 10W to 60W	2 = 2 FT. 3 = 3FT. 4 = 4FT. 8 = 8FT.	30K = 3000K 35K = 3500K 40K = 4000K 50K = 5000K	N = No Dimming 10 = 0-10V P = Power Line 50 = 50/50 Dimming	S = Standard 4.25 Inches C = Custom Enter Dimension to the nearest 1/8th inch. Example: C4.75 = 4 3/4 Inches	Blank = No Option OC = Occupancy Sensor OCBL = Occupancy Bi-Level Dimming OCAL = Occupancy Bi-Level Dimming with Grouping				



Not all product variations listed on this page are DLC qualified. Visit $\underline{www.designlights.org/search}$ to confirm qualification.

Contact Jaykal for additional product approval.