

G4 SHOE BOX TAA VERSION PROJECT NAME: JAYKAL LED SOLUTIONS, INC. www.jaykal.net 21499 Baltimore Ave. Georgetown, DE 19947 (P) 302-295-0015 (F) 302-295-0016

PRODUCT DESCRIPTION


Jaykal's new generation shoe box fixture for outdoor application with wattage/CCT selectable function.

Wattage and color selectability is standard, allowing field tuning to meet changing project requirements. It featuring four wattage presets and three color presets and is DLC listed.

TAA Available.

FEATURES

- Wattage Selectable: From 50W to 500W
- CCT Selectable: 3000K/4000K/5000K
- 100-277VAC & 277-480VAC Input Voltage Options
- 0-10V Dimming Standard
- Photocell Optional
- Sensor Optional
- Various Mounting Brackets















JAYKAL

SPECIFICATIONS TABLE									
MODEL	JLS-G4SB-T								
INPUT VOLTAGE	100-277VAC 50-60HZ / 277-480VAC 50-60HZ								
ТҮРЕ	M1	M2	M3	M4	M5	M6	M7		
WATTAGE	50/65/80/100W	80/100/120/150W	100/120/150/200W	120/150/200/240W	150/200/240/300W	200/240/300/400W	240/300/400/500W		
EFFICACY	160lm/W @40K								
LUMENS	8,000/10,400/12,800 /16,000LM	12,800/16,000/19,20 0/24,000lm	16,000/19,200/24,0 00/32,000lm	19,200/24,000/32,0 00/38,400lm	24,000/32,000/38,40 0/48,000lm	32,000/38,400/48,00 0/64,000lm	38,400/48,000/64,00 0/80,000lm		
POWER FACTOR	>0.9								
THD	<20%								
L70 HOURS	>50,000 Hours								
CRI	>70								
CCT PRESETS	3000K / 4000K / 5000K Selectable								
DIMMING	0-10V Dimming								
DIMMING POWER RATING	<5mA								
SURGE PROTECTION	6KV								
KVOPERATING TEMP.	-40°C - 45°C								
IP RATING	WET LOCATIONS (IP66)								
IK RATING	ІКО9								
EPA	1.5	4ft²		1.95ft²	2.93ft²				
N. W (kg/lbs)	3.26kg±0.5 (7.19lbs±1.1)	:	3.94kg±0.5 (8.69lbs±1.	6.41kg±0.5 (14.13lbs±1.1)				
DIMENSION(mm/in)	463*267*75mm 1	8.23*10.57*2.95in	504*3	10*75mm 19.84*12.20	630*371*79mm 24.80*14.61*3.11in				
HOUSING	Die-casting Aluminum								
LENS	Polycarbonate								
WARRANTY	5 Year Standard Warranty, 10 Year Optional								
CERTIFICATIONS	UL/DLC/CE/ROHS								



JAYKAL

ORDERING GUIDE EXAMPLE: JLS-G4SB-T-M2-277-7MCCT-BR-SF-T3						CT-BR-SF-T3			
MODEL		WATTAGE		VOLTAGE		сст -	COLOR	MOUNTING OPTIONS	- DISTRIBUTION
JLS-G4SB-T		M1 = 50/65/80/100W M2 = 80/100/120/150W M3 = 100/120/150/200W M4 = 120/150/200/240W M5 = 150/200/240/300W M6 = 200/240/300/400W M7 = 240/300/400/500W		277 = 100-277VAC 480 = 277-480VAC		7MCCT = 3000K/4000K/5000K	BR = Bronze	SF = Slip Fitter bracket EA = EA Bracket YK = Yoke Bracket TR = Trunnion Bracket MB = 4-in-1 Multiple Bracket	T2 = Type II T3 = type III T4 = type IV T5 = type V

Accessories (SOLD SEPARATELY)

Control	s				
DESCRIPTION	MODEL NUMBER				
Photocell : 3-Pin Lighting Switch	JLS-G4SB-T-PC-3P				
Photocell: 5-Pin Expandable DALI or 0-10V Dimming	JLS-G4SB-T-PC-5P				
Photocell : Expandable DALI, 0-10V Dimming and other functions	JLS-G4SB-T-PC-7P				
Motion Sensor	JLS-G4SB-T-MS				



JAYKAL

Accessories of Mounting Brackets











SF Bracket


EA Bracket


YK Bracket


TR Bracket

4-in-1 Multiple Bracket

Photometric Diagrams








T2

T4



T5



JAYKAL

Tool-free Quick Replacement

The driver box and optical lens can be opened without tools. This is very convenient for the later maintenance of the power supply or change optical lens, saving time and costs for maintenance.





Change Lighting Angle By Changing Lens Direction

By being able to easily swap out lenses, installer can adjust the lighting options based on customer demands without having to stock multiple variations of the entire light fixture.

This flexibility can help streamline inventory management and reduce costs associated with excess inventory.





JAYKAL

Dimensional Drawings (Unit:mm/inch)

