

PROJECT NAME:

PROJECT NOTES:



### JLS-LLE-WPPA102 SERIES BLUETOOTH CONTROLLER NODE

**JAYKAL** 

**JAYKAL LED SOLUTIONS, INC.** 

Georgetown, DE 19947

(F) 302-295-0016

# www.jaykal.net 21499 Baltimore Ave.


(P) 302-295-0015

#### **PRODUCT DESCRIPTION**

The JLS-LLE-WPPA102 is an advanced Bluetooth control node engineered for seamless integration with LumaLinx sensor ecosystems. Featuring an enhanced antenna design, it achieves a superior transmission range of up to 328 feet (100 meters), making it optimal for high-mounting applications and installations requiring extended inter-node distances. The IP66-rated enclosure ensures robust protection against dust and water ingress, while its white finish is specifically designed to aesthetically complement commercial indoor luminaires. Constructed from UV-rated polycarbonate material, the JLS-LLE-WPPA102 offers exceptional durability and resistance to environmental degradation, ensuring long-term performance in diverse lighting control applications.

#### **FEATURES**

- Simplified reset: Factory settings restored by 3-second magnet proximity
- Seamless connectivity: Enables wireless linking with other LumaLinx devices
- Environmental protection: IP66-rated for wet location applications
- Durable construction: UV-rated polycarbonate housing with white finish
- Extended range: Enhanced antenna design with Bluetooth transmission up to











Revised 11/13/24





| HIGHE WIDDA102 CEDIES |  |
|-----------------------|--|

**SPECIFICATIONS TABLE** 

| JLS-LLE-WPPA102 SERIES |                               |  |
|------------------------|-------------------------------|--|
| INPUT VOLTAGE          | 12VDC                         |  |
| INPUT CURRENT          | 41mA Max                      |  |
| INPUT POWER            | 0.5W                          |  |
| OUTPUT CURRENT         | 10mA Max                      |  |
| OUTPUT POWER           | 0.1W                          |  |
| DIMMING                | Class 2, 0-10V DC 10mA Max    |  |
| SINKING CURRENT        | 10mA Max                      |  |
| BLUETOOTH TRANSMIT     | 100ft Max                     |  |
| RADIO FREQUENCY        | 2.4GHz ± 75MHz                |  |
| BLUETOOTH VERSION      | 5.0                           |  |
| HOUSING MATERIAL       | UL 94-5VA                     |  |
| INDOOR/OUTDOOR USE     | Indoor Use                    |  |
| OPERATING TEMPERATURE  | -30°C to 65°C, -22°F to 149°F |  |
| STORAGE TEMPERATURE    | -30°C to 85°C, -22°F to 185°F |  |
| IP RATING              | IP66/Wet Location             |  |
| COLOR                  | White                         |  |
| WARRANTY               | 5 Years                       |  |
| COMPLIANCE             | UL8750, UL1376, RoHS          |  |

Due to our continued efforts to improve our products, specifications are subject to change without notice.

### **Ordering Guide**

| MODEL                  | BASE      | COLOR | BLUETOOTH VERSION | DESCRIPTION               |
|------------------------|-----------|-------|-------------------|---------------------------|
| JLS-LLE-WPPA102-BH4.B1 | BH4       | White | 5.0               |                           |
| JLS-LLE-WPPA102-BH4.A0 | BH4       | White | 4.2               |                           |
| JLS-LLE-WPPA102-AUX.A0 | AUX       | White | 4.2               | Bluetooth Controller Node |
| JLS-LLE-WPPA102-AUX.B1 | AUX       | White | 5.0               | Bluetooth Controller Node |
| JLS-LLE-WPPA102-Z10.A0 | Zhaga Z10 | White | 5.0               |                           |
| JLS-LLE-WPPA102-Z10.B1 | Zhaga Z10 | White | 5.0               |                           |






ΙΔΥΚΑΙ

### **Accessory Ordering Guide**

| MODEL            | ТҮРЕ              | DESCRIPTION                  |
|------------------|-------------------|------------------------------|
| JLS-LLE-SC01-AUX | Base              | AUX Receptacle               |
| JLS-LLE-BH4      | Base              | BH4 Receptacle               |
| JLS-LLE-SC03-AUX | Accessory/Adapter | AUX Socket Extension Adapter |

#### **WIRING**




| Socket Mounting Dimensions |              |                |
|----------------------------|--------------|----------------|
| Size                       | T.P.I - inch | Major Dia inch |
| R1/2                       | 14           | 0.825          |


#### **DIMENSIONS**

#### Unit:inch/mm

JLS-LLE-WPPA102-BH4-W

0.92"
23.5mm









## JAYKAL


JLS-LLE-BH4W


#### **ACCESSORIES DIMENSIONS**


JLS-LLE-WSC03-AUX

Zhaga Z10 (By Others) JLS-LLE-WSC01-AUX













| Socket Mounting Dimensions |              | <sup>1</sup> / <sub>2</sub> inch US standard knockout |
|----------------------------|--------------|---|
| Size                       | T.P.I - inch | Major Dia inch  |
| R1/2                       | 14           | 0.825   |





#### **TRANSMISSION**

























**JAYKAL** 

#### **TRANSMISSION**

| Wireless Signal Strength |           |  |
|--------------------------|-----------|--|
| Transmission<br>Distance | RSSI(dbm) |  |
| 82ft(25m)                | -76       |  |
| 164ft(50m)               | -79       |  |
| 246ft(75m)               | -87       |  |
| 328ft(100m)              | -90       |  |

Note: The test transmission distance of two JLS-LLE-WPPA102-W

#### **PRODUCT LABEL**



JLS-LLE-WPPA102-BH4.B1





JLS-LLE-WPPA102-Z10.B1

The Bluetooth word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by LumaLinx is under license. Other trademarks and trade names are those of their respective owners.

JLS-LLE-WPPA102-AUX.B1

Input/Output type: Class2, Output load type: Specific load-0-10V

#### **APP DOWNLOAD**



