

LED PL LAMP



JAYKAL

PROJECT NAME:

JAYKAL LED SOLUTIONS, INC.

www.jaykal.net

PROJECT NOTES:

21499 Baltimore Ave.

Georgetown, DE 19947

(P) 302-295-0015

(F) 302-295-0016

FEATURES

- ◆ Lamp Base Compatible for GU24, E26, G24q, GX23
- ◆ Universal voltage: 100V– 277V applications
- ◆ UL&CUL Listed/Classified
- ◆ Beam angle-120°light emitting area



COMPARISON

POWER	6W	8W	11W
LUMENS	560 – 620 LM	790 - 850 LM	1180 - 1120 LM
EFFICACY	93-103 lm/W	98-106 lm/W	107-115 lm/W
CRI (Ra>)	83	83	83
(L70) LIFE	50,000 Hrs.	50,000 Hrs.	50,000 Hrs.



Revised 3/19/24

Specifications are typical values and may change without notification

efficiency. illuminated.

LED PL LAMP



JAYKAL

JLS-PL-H-6 SPECIFICATIONS	
INPUT VOLTAGE	AC100-277V (50~60Hz)
INPUT POWER	6W
LUMENS	560 – 620 LM
CCT	2700K/3000K/4000K/5000K
BASE	GU24/E26/G24Q/GX23
BEAM ANGLE	120°
CRI	83
LENS	Frosted or Clear
CERTIFICATIONS	UL& cUL, CE & ROHS, DLC
WARRANTY	5 Years
DIMENSIONS	5.30 X 1.35 in.

JLS-PL-H-8 SPECIFICATIONS	
INPUT VOLTAGE	AC100-277V (50~60Hz)
INPUT POWER	8W
LUMENS	790 – 850 LM
CCT	2700K/3000K/4000K/5000K
BASE	GU24/E26/G24Q/GX23
BEAM ANGLE	120°
CRI	83
LENS	Frosted or Clear
CERTIFICATIONS	UL& cUL, CE & ROHS, DLC
WARRANTY	5 Years
DIMENSIONS	6.30 X 1.35 in.

(P) 302-295-0015 | (E) sales@jaykal.net | (W) www.jaykal.net

Specifications are typical values and may change without notification

efficiency. illuminated.

LED PL LAMP



JAYKAL

JLS-PL-H-11 SPECIFICATIONS	
INPUT VOLTAGE	AC100-277V (50~60Hz)
INPUT POWER	11W
LUMENS	1180 – 1270 LM
CCT	2700K/3000K/4000K/5000K
BASE	GU24/E26/G24Q/GX23
BEAM ANGLE	120°
CRI	83
LENS	Frosted or Clear
CERTIFICATIONS	UL& cUL, CE & ROHS, DLC
WARRANTY	5 Years
DIMENSIONS	7.20 X 1.35 in.

ORDERING INFORMATION				EXAMPLE: JLS-PL-H-6-MCCT-E26				
MODEL	-	TYPE	-	WATTAGE	-	CCT	-	BASE
JLS-PL		H = Horizontal		6 = 6W 8 = 8W 11 = 11W		27K = 2700K 30K = 3000K 40K = 4000K 50K = 5000K		E26 = E26 Lamp Base GU24 = GU24 Lamp Base GX23 = GX23 Lamp Base G24Q = G24Q Lamp Base

(P) 302-295-0015 | (E) sales@jaykal.net | (W) www.jaykal.net

Specifications are typical values and may change without notification

efficiency. illuminated.