

| T8 TYPE B LED TUBE - 0-10V DIMMING | JAYKAL |
|------------------------------------|----------------------------|
| PROJECT NAME: | JAYKAL LED SOLUTIONS, INC. |
| | www.jaykal.net |
| PROJECT NOTES: | 21499 Baltimore Ave. |
| | Georgetown, DE 19947 |
| | (P) 302-295-0015 |
| | (F) 302-295-0016 |

PRODUCT DESCRIPTION

High Efficacy Type B lamps with 0-10V dimming capability provides a path for controls to be installed in more environments.

FEATURES

- 0-10V Dimming Standard
- Sensor Ready Design
- EM Ready
- Single/Dual Ended Design











T8 TYPE B LED TUBE - 0-10V DIMMING

ССТ

WORKING TEMPERATURE

ENVIRONMENT

ΙΔΥΚΔΙ

| SPECIFICATIONS TABLE | | | | | | | |
|----------------------|------------------------------|---------|---------|--|--|--|--|
| TYPE B 0-10V | | | | | | | |
| INPUT VOLTAGE | 120-277VAC 50/60hz | | | | | | |
| LENGTH | 2FT | 4FT | | | | | |
| WATTAGE | 8W | 12W | 10.5W | | | | |
| EFFICACY | 131lm/W | 125lm/W | 157lm/W | | | | |
| LUMENS | 1,050 | 1,500 | 1,650lm | | | | |
| POWER FACTOR | >0.96 | | | | | | |
| THD | <20% | | | | | | |
| VIEWING ANGLE | 200° | | | | | | |
| WIRING SCHEME | Single Ended or Double Ended | | | | | | |
| CRI | 83 | | | | | | |
| L70 HOURS | >50,000 | | | | | | |

3000K/3500K/4000K/5000K

-20°C - +45°C

Dry/Damp

| ORDERING GUIDE JLS-4-840K-F-10.5-SD-10 | | | | | | | | | | |
|--|---|-------------------|---|---------------------|---|------------------------|---|-----------------------------------|---|-------------------|
| MODEL | - | LENGTH | - | сст | - | WATTS | - | ТҮРЕ | - | DIMMING |
| JLS | | 2 = 2 Foot | | 830K = 3000K | | 8 = 8W* | | SD = Single Ended or Double Ended | | 10 = 0-10V |
| | | 3 = 3 Foot | | 835K = 3500K | | 12 = 10W** | | | | |
| | | 4 = 4 Foot | | 840K = 4000K | | 10.5 = 10.5W*** | | | | |
| | | | | 850K = 5000K | | * 2 Foot Only | | | | |
| | | | | | | ** 3 Foot Only | | | | |
| | | | | | | *** 4 Foot Only | | | | |
| | | | | | | | | | | |




T8 TYPE B LED TUBE - 0-10V DIMMING


JAYKAL

| Product | Length Pin to Pin (in.) | Length Base to Base (in.) | Diameter (in.) |
|---------|-------------------------|---------------------------|----------------|
| 4 Foot | 47.71 | 47.165 | 1.125 |
| 3 Foot | 35.55 | 23.11 | 1.125 |
| 2 Foot | 23.77 | 23.14 | 1.125 |

WIRING DIAGRAMS



Single ended 0-10V dimming



Single&Double ended 0-10V dimming